

1. PRODUCT AND COMPANY IDENTIFICATION

- 1.1 Product Name:** Alcohol, Ethyl Denatured, 80%
Part Number: 10843
CAS-No.: Not applicable
SDS Number: 2190
- 1.2 Recommended Use:** Laboratory Chemicals
- 1.3 Company:** Newcomer Supply
 2505 Parview Road
 Middleton, WI 53562 USA
- Telephone:** 1-800-383-7799
Fax: 1-608-831-0866
Website: www.newcomersupply.com
Email: newly@newcomersupply.com

24 HOUR EMERGENCY CONTACT
 CALL CHEMTREC: 1-800-424-9300
 Contact CHEMTREC only in the event of an emergency involving a chemical spill, leak, fire, exposure or other accident.

2. HAZARD(S) IDENTIFICATION

- 2.1 Classification of the substance or mixture**
 GHS Classification, (in accordance with 29 CFR1910.1200)
 Flammable liquid, Category 2
 Serious Eye Damage/Eye irritation, Category 2A
 Acute toxicity (oral), Category 4
 Acute toxicity (dermal), Category 4
 Acute toxicity (inhalation), Category 4
 Carcinogenicity, Category 2

2.2 GHS Label elements

Signal Word DANGER

Pictogram



Hazard Statement(s):

- Highly flammable liquid and vapour
- Causes serious eye irritation
- Suspected of causing cancer
- Harmful if swallowed
- Harmful in contact with skin
- Harmful if inhaled

Precautionary Statement(s):

Prevention:

- Keep away from heat/sparks/open flames/hot surfaces – No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof fume hood/electrical/ventilating/light/.../equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Wear protective gloves/protective clothing/eye protection/face protection
- Wash skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Avoid breathing dust/fume/gas/mist/vapours/spray
- Use only outdoors or in a well-ventilated area

Response:

Version 1.0

- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- Wash contaminated clothing before reuse
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
- If eye irritation persists get medical advice/attention
- Call a POISON CENTER or doctor/physician if you feel unwell
- Rinse mouth
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Specific treatment: see first aid measures in section 4
- IF exposed or concerned: Get medical advice/attention
- In case of fire use carbon dioxide, dry chemical or alcohol-resistant foam.

Storage:

- Store in a well ventilated place. Keep cool
- Store locked up

Disposal:

- Dispose of contents/ container to an approved waste disposal plant.

2.3 Description of any hazards not otherwise classified None

2.4 >1% of mixture with unknown acute toxicity None

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixture

Hazardous Components

| Component | | Concentration |
|-----------|------------------------|---------------|
| Name | Ethyl Alcohol | |
| CAS-No. | 64-17-5 | 69% |
| Name | Isopropyl Alcohol | |
| CAS-No. | 67-63-0 | 7.2% |
| Name | Methyl Alcohol | |
| CAS-No. | 67-56-1 | 3.2% |
| Name | Methyl Isobutyl Ketone | |
| CAS-No. | 108-10-1 | 0.8% |

4. FIRST-AID MEASURES

4.1 Description of necessary measures

Inhalation (breathing)

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin Contact

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a POISON CENTER or doctor/physician if you feel unwell.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion (swallowed)

IF SWALLOWED: Rinse mouth. Call a POISON CENTER or doctor/physician if you feel unwell.

4.2 Most important symptoms and or effects, acute and delayed

The most important symptoms/effects are presented in Section 2 and or Section 11.

Version 1.0

4.3 Indication of any immediate medical attention and special treatment needed

No data available

5. FIRE-FIGHTING MEASURES
5.1 Suitable extinguishing media

Carbon dioxide, dry chemical, water spray, alcohol-resistant foam.

5.2 Specific hazards arising from the substance or mixture

No data available

5.3 Protective equipment and precautions for fire-fighters

Wear a positive-pressure self-contained breathing apparatus if necessary. Wear chemical resistant clothing as recommended by clothing manufacturer.

NFPA Rating

| | | |
|-----------|-----------|------------|
| Health | Fire | Reactivity |
| hazard: 2 | hazard: 3 | hazard: 0 |

6. ACCIDENTAL RELEASE MEASURES
6.1 Personal precautions, protective equipment and emergency procedures

Apply personal protective equipment (see Section 8). Use in a properly ventilated area. Avoid breathing vapors. Avoid skin contact. Avoid eye contact. Wash hands after use. In case of large spill, remove personnel to a safe area. Keep product away from heat, flame, ignition sources, and reactive materials. Avoid accumulation of vapor to form explosive concentration. Pay particular attention to low areas where vapor accumulates more easily.

6.2 Methods and material for containment and cleaning up

Apply personal protective equipment (see Section 8). Contain spill. Prevent further leakage if possible and safe to do so. Ensure proper ventilation. For small amounts, wipe or absorb spill using inert material and dispose of according to local regulations. For large amounts, evacuate area and limit access. Prevent entry of material into sewage drains and confined areas. Dispose of any contaminated materials according to local regulations. Eliminate sources of ignition.

7. HANDLING AND STORAGE
7.1 Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces – No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection.

7.2 Conditions for safe storage, including any incompatibilities

Refer to Section 2.2 for proper storage temperature. Store the tightly closed container in a cool, dry, well-ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION
8.1 Control Parameters

Components with limit values that require monitoring at the workplace

| Component | CAS-No. | Regulatory | Value | Parameters |
|---------------|---------|------------|-------|------------------------------------|
| Ethyl Alcohol | 64-17-5 | OSHA PEL | TWA | 1000 ppm (1900 mg/m ³) |
| | | ACGIH TLV | TWA | 1000 ppm (1880 mg/m ³) |
| | | NIOSH REL | TWA | 1000 ppm (1900 mg/m ³) |

| Component | CAS-No. | Regulatory | Value | Parameters |
|----------------|---------|------------|-------|----------------------------------|
| Methyl Alcohol | 67-56-1 | OSHA PEL | TWA | 200 ppm (980 mg/m ³) |

Version 1.0

| | | | | |
|--|--|-----------|------|------------------------------------|
| | | ACGIH TLV | STEL | 200 ppm (1,230 mg/m ³) |
| | | ACGIH TLV | STEL | 50 ppm (1,230 mg/m ³) |
| | | NIOSH REL | TWA | 200 ppm (980 mg/m ³) |
| | | NIOSH REL | STEL | 250 ppm (980 mg/m ³) |

| Component | CAS-No. | Regulatory | Value | Parameters |
|-------------------|---------|------------|-------|------------------------------------|
| Isopropyl Alcohol | 67-63-0 | OSHA PEL | TWA | 400 ppm (980 mg/m ³) |
| | | ACGIH TLV | TWA | 400 ppm (983 mg/m ³) |
| | | ACGIH TLV | STEL | 500 ppm (1,230 mg/m ³) |
| | | NIOSH REL | TWA | 400 ppm (980 mg/m ³) |
| | | NIOSH REL | STEL | 500 ppm (980 mg/m ³) |

| Component | CAS-No. | Regulatory | Value | Parameters |
|------------------------|----------|------------|-------|----------------------------------|
| Methyl Isobutyl Ketone | 108-10-1 | OSHA PEL | TWA | 100 ppm (410 mg/m ³) |
| | | ACGIH TLV | TWA | 50 ppm (205 mg/m ³) |
| | | ACGIH TLV | STEL | 75 ppm (307 mg/m ³) |
| | | NIOSH REL | TWA | 50 ppm (205 mg/m ³) |
| | | NIOSH REL | STEL | 75 ppm (300 mg/m ³) |

8.2 Exposure Controls

Appropriate engineering controls

Use in a properly ventilated area. Remove/wash before reuse contaminated clothing. Wash hands upon exiting work premises. Use product in an appropriately designated fume hood. Take measures to keep concentrations below acceptable limits.

8.3 Personal Protective Equipment

Eye/Face protection

Wear chemical safety goggles and/or a full face shield if splashing is possible. Keep eye wash fountain nearby.

Skin Protection

Wear chemical-resistant gloves. Gloves should be resistant to components of product. Refer to glove manufacturer for appropriate type and glove thickness.

Body Protection

No data available

Respiratory Protection

Version 1.0

Respirators should only be used if the employer has implemented a written program that takes into account workplace conditions, requirements for worker training, respirator fit testing, and medical exams, as described in the OSHA Respiratory Protection Standard (29 CFR 1910.134).

Ethyl Alcohol: Where the potential exists for exposure over 1,000 ppm: use a NIOSH approved supplied-air respirator with a full facepiece operated in a pressure-demand or other positive-pressure mode. For increased protection use in combination with an auxiliary self-contained breathing apparatus or an emergency escape air cylinder.

Exposure to 3,300 ppm is immediately dangerous to life and health. If the possibility of exposure above 3,300 ppm exists, use a NIOSH approved self-contained breathing apparatus with a full facepiece operated in a pressure-demand or other positive-pressure mode equipped with an emergency escape air cylinder.

In case of emergency, entry into or escape from unknown concentrations select the highest level approved respiratory protection available.

Other Information

None

9. PHYSICAL AND CHEMICAL PROPERTIES
9.1 Information on basic physical and chemical properties

| | |
|---|--|
| Physical state | Colorless liquid |
| Odor | Alcoholic odor |
| Odor threshold | No data available |
| pH | No data available |
| Melting point/freezing point | No data available |
| Initial boiling point and boiling range | 78-80°C (172-176°F) |
| Flash point | 13°C (55.4°F) Closed cup (Ethyl Alcohol) |
| Evaporation rate | 1.7 (Ethyl Alcohol) |
| Flammability (solid, gas) | Liquid is flammable |
| Upper flammability or explosive limits | 19% |
| Lower flammability or explosive limits | 3% |
| Vapor pressure | No data available |
| Vapor density | 1.6 (Ethyl Alcohol) |
| Relative density | 0.789 |
| Solubility(ies) | Miscible with water and many organic liquids |
| Partition coefficient: n-octanol/water | No data available |
| Auto-ignition temperature | No data available |
| Decomposition temperature | No data available |
| Viscosity | No data available |

10. STABILITY AND REACTIVITY
10.1 Reactivity

No data available

10.2 Chemical stability

Stable in a closed container within label-specified storage temperature and expiration date.

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Heat, sparks, open flame, and ignition sources.

10.5 Incompatible materials

Version 1.0

Strong oxidizers, potassium dioxide, bromine pentafluoride, acetyl bromide, acetyl chloride, platinum, sodium concentrated sulfuric acid, potassium and hydrogen peroxides, platinum black, calcium hypochlorite, silver oxide, ammonia, nitric acid, mercuric nitrate, silver nitrate, magnesium perchlorate, isocyanates, mineral acids, and chloroform.

10.6 Hazardous decomposition products

No data available

11. TOXICOLOGICAL INFORMATION**11.1 Information on toxicological effects****Inhalation exposure**

Inhaling ethyl alcohol, methyl alcohol, and isopropyl alcohol can irritate the nose, throat and lungs causing coughing and/or shortness of breath. Breathing methyl isobutyl ketone can irritate the nose and throat causing coughing and wheezing. Breathing methyl isobutyl ketone vapor can cause headache, loss of appetite, nausea, vomiting, and diarrhea.

Oral exposure

Oral exposure to ethyl alcohol, methyl alcohol, and isopropyl alcohol can cause headache, drowsiness, nausea and vomiting, and unconsciousness. It can also affect concentration and vision.

Dermal exposure

Contact can irritate the skin.

Skin corrosion/irritation

Prolonged or repeated exposure can cause drying and cracking of the skin with peeling, redness and itching.

Serious eye damage/irritation

Contact can irritate and burn the eyes.

Respiratory or skin sensitization

Inhaling ethyl alcohol, methyl alcohol, and isopropyl alcohol can irritate the nose, throat and lungs causing coughing and/or shortness of breath.

Germ Cell mutagenicity

No data available

Reproductive toxicity

Repeated oral exposure to ethyl alcohol may cause spontaneous abortions, as well as birth defects and other developmental problems. This condition is referred to as "fetal alcohol syndrome." There is limited evidence that oral exposure to ethyl alcohol may decrease fertility in males.

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

Repeated high exposure may affect the liver and the nervous system.

Aspiration hazard

No data available

Acute toxicity (Ethyl Alcohol)

LD50 rat oral 3450 mg/kg

LD50 mouse oral 7060 mg/kg

LC50 rat inhalation 20000 ppm/10H

LC50 mouse inhalation 20363 ppm/4H

Version 1.0

Carcinogenicity

IARC: Methyl Isobutyl Ketone: Group 2B Possible human carcinogen

NTP: None of the components are listed

OSHA: None of the components are listed

Additional information

RTECS: No data available

12. ECOLOGICAL INFORMATION
12.1 Ecotoxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS
13.1 Waste disposal methods
Contents

Dispose of contents in a safe manner to comply with local, state and federal regulations. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of packaging in a safe manner to comply with local, state and federal regulations. Contact a licensed professional waste disposal service to dispose of this material.

14. TRANSPORT INFORMATION
14.1 DOT (US)

| | |
|------------------------------|-------------------|
| UN-Number | 1170 |
| Proper shipping name | Ethanol |
| Hazard class | 3 |
| Packing group | II |
| Environmental hazards | No data available |

15. REGULATORY INFORMATION
15.1 No data available

16. OTHER INFORMATION

Preparation Information

Newcomer Supply Inc.

800-383-7799

www.newcomersupply.com

Copyright © Newcomer Supply Inc. All rights reserved.